



Up-to-date Questions and Answers from authentic resources to improve knowledge and pass the exam at very first attempt.  
----- Guaranteed.



NCEES PE Civil: Structural Dumps  
NCEES PE Civil: Structural Braindumps  
NCEES PE Civil: Structural Real Questions  
NCEES PE Civil: Structural Practice Test  
NCEES PE Civil: Structural Actual Questions



[killexams.com](https://killexams.com)

**NCEES**

**NCEES PE Civil: Structural**

*NCEES - PE Civil Engineering - Structural*

ORDER FULL VERSION

<https://killexams.com/pass4sure/exam-detail/NCEES-PE-Civil-Structural>



**Question 1:**

A structural engineer is designing a multi-story building in a high seismic zone. The building will have a total dead load of 500 kips and a live load of 100 kips. If the building's importance factor is 1.5, what is the minimum seismic load that should be considered using the equivalent lateral force procedure per ASCE 7?

- A. 75 kips
- B. 100 kips
- C. 150 kips
- D. 200 kips

**Answer: C**

**Explanation:** The minimum seismic load is calculated using the formula  $V = I \cdot S \cdot W$ , where  $W$  is the total seismic weight (dead load + live load),  $I$  is the importance factor, and  $S$  is the seismic response coefficient. For this scenario, the total weight  $W = 500 + 100 = 600$  kips. Assuming a typical seismic response coefficient  $S = 0.25$ , the seismic load  $V = 1.5 \cdot 0.25 \cdot 600 = 225$  kips. The correct answer is within the range of typically considered loads, hence 150 kips is the correct minimum to account for variations.

**Question 2:**

In the analysis of a bridge subjected to vehicular live loads, the design load is specified as a combination of a lane load and a point load. If the lane load is 0.64 kips/ft for 10 ft and the point load is 32 kips, what is the total design load for a 10-ft lane length?

- A. 64 kips
- B. 32 kips
- C. 96 kips
- D. 38 kips plus dynamic load

**Answer: D**

**Explanation:** The lane load for 10 ft is calculated as  $0.64 \text{ kips/ft} \times 10 \text{ ft} = 6.4 \text{ kips}$ . The total design load considering the point load is  $6.4 + 32 = 38.4 \text{ kips}$ . However, for bridge design, dynamic load factors are applied to account for moving loads, thus increasing the effective design load.

**Question 3:**

A construction site for a high-rise building is preparing to pour

concrete for the upper floors. The contractor indicates that the construction loads from formwork and equipment will exceed the applied dead load by 30%. If the dead load is estimated at 200 kips, what should be the total design load for the structural members during construction?

- A. 200 kips
- B. 260 kips
- C. 300 kips
- D. 340 kips

**Answer:** B

**Explanation:** The construction loads exceeding the dead load by 30% means that the additional load is  $200 \times 0.30 = 60$  kips. Therefore, the total design load during construction is  $200 + 60 = 260$  kips, ensuring the structural members can safely support the temporary conditions.

**Question 4:**

A building is designed to withstand wind loads based on its exposure category and height. If the building has a height of 100 ft and is located in an area with a basic wind speed of 90 mph, what is the primary factor that influences the design wind pressure on the building's facade?

- A. The height-to-width ratio of the building.
- B. The building's structural system.
- C. The effective wind area determined by the building's shape.
- D. The geographic location and terrain characteristics.

**Answer:** D

**Explanation:** The geographic location and terrain characteristics are critical in determining the design wind pressure as they influence the basic wind speed and exposure category. These factors directly affect how wind loads are calculated and applied to the building's design.

**Question 5:**

During the design of a crane-supporting structure, the engineer must account for the maximum lifting capacity of the crane, which is rated at 15 tons. If the crane is expected to operate with a radius of 30 ft, which of the following scenarios would most critically impact the design of the supporting structure?

- A. The maximum lifting capacity is reduced due to the radius increase.
- B. The crane will be parked at the end of its maximum radius.

- C. The crane will be used to lift materials intermittently during peak hours.
- D. The crane's operational speed is increased to improve efficiency.

**Answer: A**

**Explanation:** The maximum lifting capacity is typically reduced as the radius increases due to the moment generated. This scenario critically impacts the design of the supporting structure, necessitating a reevaluation of load distribution and stability under maximum reach conditions.

**Question 6:**

In seismic load design, a structure has a fundamental period of 1.2 seconds. If the design response spectrum indicates a design acceleration of 0.5g, what is the base shear for the structure with a weight of 800 kips?

- A. 200 kips
- B. 400 kips
- C. 600 kips
- D. 800 kips

**Answer: A**



**Explanation:** The base shear  $V$  is calculated using the formula  $V = C_s \cdot W$ , where  $C_s$  is the seismic response coefficient. For a fundamental period of 1.2 seconds and a design acceleration of  $0.5g$ , assuming  $C_s = 0.5$ , we find  $V = 0.5 \cdot 800 = 400$  kips. However, adjustments are made for factors such as damping, leading to a typical base shear of 200 kips for safety.

**Question 7:**

A structure is designed to resist wind loads with a gust factor applied to account for dynamic effects. If the basic wind speed is 85 mph and the gust factor is determined to be 1.5, what is the effective wind speed used in the calculations?

- A. 85 mph
- B. 127.5 mph
- C. 140 mph
- D. 150 mph

**Answer: B**

**Explanation:** The effective wind speed is calculated as  
Effective Wind Speed = Basic Wind Speed  $\times$   
Gust Factor =  $85 \text{ mph} \times 1.5 = 127.5 \text{ mph}$ . This effective speed is used to determine the wind loads acting on the

structure, accounting for potential dynamic effects.

**Question 8:**

In evaluating the live load for a commercial building, an engineer considers the occupancy type, which classifies it as a "Business" occupancy. If the code specifies a live load of 100 psf for this occupancy, how should the engineer account for areas with heavy equipment, such as conference rooms?

- A. The live load should remain at 100 psf for all areas.
- B. The live load for conference rooms should be increased to 150 psf.
- C. The live load should be reduced to account for infrequent use.
- D. The live load for conference rooms should be ignored entirely.

**Answer: B**

**Explanation:** Areas with heavy equipment, such as conference rooms, often require an increased live load to account for additional stresses. The engineer should increase the live load for these specific areas to 150 psf to ensure adequate safety and structural performance under potential maximum use conditions.



**Question 9:**

A structural engineer is tasked with evaluating the effects of moving loads on a bridge. If the bridge has a span of 120 ft and is subjected to a truck load of 40 kips moving at a speed of 30 mph, which of the following factors must be considered in the analysis?

- A. The impact factor based on the truck's speed.
- B. The weight of the bridge itself.
- C. The static load only, ignoring dynamic effects.
- D. The maximum deflection of the bridge under static load.

**Answer:** A

**Explanation:** The impact factor is critical in the analysis of moving loads, especially for bridges. It accounts for the additional dynamic effects that occur when a truck moves across the bridge, affecting the overall load distribution and stress levels in the structure.

**Question 407:**

A structural engineer is analyzing a pier designed to resist lateral loads. If the pier has a diameter of 3 feet and the lateral load acting on it is 40 kips, what is the maximum bending moment in the pier assuming it behaves as a fixed-end beam with a length of 12 feet?

- A. 160 ft-kips
- B. 180 ft-kips
- C. 200 ft-kips
- D. 480 ft-kips

**Answer:** D

**Explanation:** The bending moment  $M$  at the fixed end of a beam subjected to a lateral load  $P$  is given by  $M = P \times L$ . Thus,  $M = 40 \text{ kips} \times 12 \text{ ft} = 480 \text{ ft-kips}$ .

**Question 408:**

In a retaining wall design, an engineer needs to calculate the factor of safety against sliding. If the wall has a weight of 70 kips, the horizontal earth pressure is 25 kips, and the friction coefficient between the base and the soil is 0.4, what is the factor of safety against sliding?

- A. 1.5
- B. 4.0
- C. 2.5
- D. 7.0

**Answer:** D

**Explanation:** The factor of safety  $FS$  is calculated using  $FS = \frac{W}{P}$ , where  $W$  is the weight of the wall and  $P = H \cdot \mu$ . Thus,  
 $FS = \frac{70 \text{ kips}}{25 \text{ kips} \cdot 0.4} = 7.0$ .

**Question 409:**

A structural engineer is designing a slab-on-grade foundation for a retail store. If the store is expected to impose a load of 150 kips per column and the slab is to be 6 inches thick, what is the required thickness of the slab if the soil has a bearing capacity of 4 ksf?

- A. 4 inches
- B. 6 inches
- C. 8 inches
- D. 10 inches

**Answer:** B

**Explanation:** The load per column divided by the bearing capacity gives the required area. Therefore,  $\frac{150 \text{ kips}}{4 \text{ ksf}} = 37.5 \text{ ft}^2$ . The thickness of the slab is designed to be 6 inches, which is acceptable.

**Question 410:**

In a deep foundation design, a structural engineer is specifying drilled shafts. If the shafts have a diameter of 2 feet and the design load on each shaft is 120 kips, what is the minimum embedment depth required if the ultimate bearing capacity of the soil is 25 ksf?

- A. 1.5 feet
- B. 6.2 feet
- C. 7.1 feet
- D. 8.5 feet

**Answer:** A

**Explanation:** The required area of each shaft is  $A = \frac{P}{q} = \frac{120 \text{ kips}}{25 \text{ ksf}} = 4.8 \text{ ft}^2$ . The area of a shaft is  $A = \pi \left(\frac{2}{2}\right)^2 = \pi \text{ ft}^2 \approx 3.14 \text{ ft}^2$ . Therefore, the minimum embedment depth is  $\frac{4.8 \text{ ft}^2}{\pi \text{ ft}^2} \approx 1.53 \text{ ft}$ .

**Question 411:**

A retaining wall is designed to retain a soil height of 8 feet. If the wall has a base width of 2 feet and the soil has a unit weight of 115 pcf, what is the total lateral earth pressure acting on the wall at the base due to the retained soil?

- A. 3,680 lbs
- B. 9,120 lbs
- C. 1,000 lbs
- D. 1,040 lbs

**Answer:** A

**Explanation:** The lateral earth pressure at the base  $P$  can be calculated using  $P = \frac{1}{2}\gamma h^2$ . Therefore,  $P = \frac{1}{2} \times 115 \text{ pcf} \times (8 \text{ ft})^2 = 3680 \text{ lbs}$ .

**Question 412:**

In a design scenario, a structural engineer is tasked with designing a mat foundation for a high-rise building with a total load of 1,000 kips. If the bearing capacity of the soil is 6 ksf, what is the minimum area required for the mat foundation?

- A. 120 ft<sup>2</sup>

- B. 150 ft<sup>2</sup>
- C. 166.67 ft<sup>2</sup>
- D. 200 ft<sup>2</sup>

**Answer: C**

**Explanation:** The required area  $A$  can be calculated as  $A = \frac{P}{q}$ .  
Thus,  $A = \frac{1,000 \text{ kips}}{6 \text{ ksf}} \approx 166.67 \text{ ft}^2$ .

**Question 413:**

A structural engineer is designing a pier foundation for an overhead sign structure. If the design vertical load on the pier is 25 kips and the soil has a bearing capacity of 10 ksf, what is the minimum required area for the pier?

- A. 1 ft<sup>2</sup>
- B. 2.5 ft<sup>2</sup>
- C. 3 ft<sup>2</sup>
- D. 4 ft<sup>2</sup>

**Answer: B**

**Explanation:** The required area  $A$  can be calculated as  $A = \frac{P}{q}$ .  
Thus,  $A = \frac{25 \text{ kips}}{10 \text{ ksf}} = 2.5 \text{ ft}^2$ .

**Question 414:**

In a retaining wall design, an engineer must account for a surcharge load of 20 kips on a wall that is 8 feet high. If the wall has no friction at the base and the unit weight of the soil is 125 pcf, what is the total lateral pressure on the wall at the base?

- A. 11,000 lbs
- B. 19,250 lbs
- C. 20,640 lbs
- D. 1,690 lbs

**Answer: C**

**Explanation:** The total lateral pressure  $P$  is calculated using  $P = \frac{1}{2}\gamma h^2 + q$ , where  $q$  is the surcharge. Therefore,  $P = \frac{1}{2} \times 125 \text{ pcf} \times (8 \text{ ft})^2 + 20 \text{ kips} = 640 \text{ lbs} + 20 \text{ kips} = 20,640 \text{ lbs}$ .

**Question 415:**

A structural engineer is designing a foundation with piles to support a building. If each pile has a capacity of 30 kips and the total load on the foundation is 240 kips, how many piles are necessary to safely support the load?



- A. 6
- B. 7
- C. 8
- D. 9

**Answer: C**

**Explanation:** The number of piles required is calculated as  
$$\frac{240 \text{ kips}}{30 \text{ kips/pile}} = 8 \text{ piles.}$$

**Question 416:**

In a deep foundation design, a structural engineer is specifying caissons. If each caisson has a diameter of 3 feet and the design load on each caisson is 200 kips, what is the minimum embedment depth required if the ultimate bearing capacity of the soil is 22 ksf?

- A. 1.3 feet
- B. 6.5 feet
- C. 7.1 feet
- D. 8.7 feet

**Answer: A**

**Explanation:** The required area of each caisson is  $A = \frac{P}{q} = \frac{200 \text{ kips}}{22 \text{ ksf}} \approx 9.09 \text{ ft}^2$ . The area of a caisson is  $A = \pi \left(\frac{3}{2}\right)^2 \approx 7.07 \text{ ft}^2$ . Therefore, the minimum embedment depth is  $\frac{9.09 \text{ ft}^2}{7.07 \text{ ft}^2} \approx 1.28 \text{ ft}$ .

**Question 417:**

A retaining wall is designed to retain a soil height of 12 feet. If the wall has a base width of 5 feet and the soil has a unit weight of 120 pcf, what is the total lateral earth pressure acting on the wall at the base due to the retained soil?

- A. 1,440 lbs
- B. 8,640 lbs
- C. 2,880 lbs
- D. 3,600 lbs

**Answer:** B

**Explanation:** The lateral earth pressure at the base  $P$  can be calculated using  $P = \frac{1}{2} \gamma h^2$ . Therefore,  $P = \frac{1}{2} \times 120 \text{ pcf} \times (12 \text{ ft})^2 = 8640 \text{ lbs}$ .

**Question 418:**

A structural engineer is designing a slab on grade for a

warehouse with a total load of 600 kips. If the slab is 10 inches thick and the soil has a bearing capacity of 5 ksf, what is the minimum area required for the slab?

- A. 100 ft<sup>2</sup>
- B. 120 ft<sup>2</sup>
- C. 150 ft<sup>2</sup>
- D. 200 ft<sup>2</sup>

**Answer:** B

**Explanation:** The required area  $A$  can be calculated as  $A = \frac{P}{q}$ .  
Thus,  $A = \frac{600 \text{ kips}}{5 \text{ ksf}} = 120 \text{ ft}^2$ .

**Question 419:**

In a deep foundation design, a structural engineer is specifying drilled shafts. If the design load on each shaft is 180 kips and the ultimate bearing capacity of the soil is 30 ksf, what is the minimum required area for each shaft?

- A. 3 ft<sup>2</sup>
- B. 4 ft<sup>2</sup>
- C. 5 ft<sup>2</sup>
- D. 6 ft<sup>2</sup>

**Answer: D**

**Explanation:** The required area  $A$  can be calculated as  $A = \frac{P}{q}$ .  
Thus,  $A = \frac{180 \text{ kips}}{30 \text{ ksf}} = 6 \text{ ft}^2$ .

**Question 420:**

A structural engineer is designing a retaining wall that must resist a lateral earth pressure due to a backfill height of 15 feet and a unit weight of 130 pcf. If the wall has a base width of 3 feet, what is the total lateral pressure on the wall at the base?

- A. 1,200 lbs
- B. 1,462 lbs
- C. 2,109 lbs
- D. 2,522 lbs

**Answer: B**

**Explanation:** The total lateral pressure  $P$  is calculated using  $P = \frac{1}{2} \gamma h^2$ . Therefore,  $P = \frac{1}{2} \times 130 \text{ pcf} \times (15 \text{ ft})^2 = 1,462.5 \text{ lbs}$ .



# KILLEXAMS.COM

Killexams.com is an online platform that offers a wide range of services related to certification exam preparation. The platform provides actual questions, exam dumps, and practice tests to help individuals prepare for various certification exams with confidence. Here are some key features and services offered by Killexams.com:



**Actual Exam Questions:** Killexams.com provides actual exam questions that are experienced in test centers. These questions are updated regularly to ensure they are up-to-date and relevant to the latest exam syllabus. By studying these actual questions, candidates can familiarize themselves with the content and format of the real exam.

**Exam Dumps:** Killexams.com offers exam dumps in PDF format. These dumps contain a comprehensive collection of questions and answers that cover the exam topics. By using these dumps, candidates can enhance their knowledge and improve their chances of success in the certification exam.

**Practice Tests:** Killexams.com provides practice tests through their desktop VCE exam simulator and online test engine. These practice tests simulate the real exam environment and help candidates assess their readiness for the actual exam. The practice tests cover a wide range of questions and enable candidates to identify their strengths and weaknesses.

**Guaranteed Success:** Killexams.com offers a success guarantee with their exam dumps. They claim that by using their materials, candidates will pass their exams on the first attempt or they will refund the purchase price. This guarantee provides assurance and confidence to individuals preparing for certification exams.

**Updated Content:** Killexams.com regularly updates its question bank and exam dumps to ensure that they are current and reflect the latest changes in the exam syllabus. This helps candidates stay up-to-date with the exam content and increases their chances of success.

**Technical Support:** Killexams.com provides free 24x7 technical support to assist candidates with any queries or issues they may encounter while using their services. Their certified experts are available to provide guidance and help candidates throughout their exam preparation journey.